

PROCUT 83

GENERAL DESCRIPTION

PROCUT 83 is a cutting oil that contains chlorine and inactive sulfur. It has excellent boundary lubrication and contains a special additive package that provides outstanding cutting properties and tool life. PROCUT 83 is recommended for use on stainless steel, ferrous, and non-ferrous metals. This versatile cutting oil is suitable for turning, reaming, and many other metal cutting applications.

The PROCUT 83 makes it easy to wash off finished parts while not staining copper or copper alloys. For the operator's ease of visibility and for general cleanliness, this oil has been formulated to be transparent and light in color. PROCUT 83 has less tendency to smoke than many competitive cutting oils, has good resistance to oxidation, and helps maintain low mist levels.

TYPICAL PROPERTIES

Viscosity @ 100°F.....	75 - 85
Gravity, API.....	27.3
Lubricity Additives	Present
Chlorine	Present
Inactive Sulfur	Present
Flash point COC °F.....	350

SHIPPING CONTAINERS

Available in 5 gallon pails, 55 gallon drums, 275 gallon totes, or bulk delivery.

HEALTH & SAFETY

Material Safety Data Sheets are available for all Wallover products. Consult the MSDS for information regarding the storage, handling and disposal of this product.

WARRANTY

All reasonable effort has been made to ensure that the information provided in this publication is accurate. No warranties are expressed or implied since the use of this product is beyond our control.