

PROCUT SS

GENERAL DESCRIPTION

PROCUT SS is a heavy-duty amber colored cutting oil. It contains sulfur, chlorine, wetting and anti-weld agents, along with premium base oils. PROCUT SS has been specially formulated with a low volatility fatty additive that has proven itself far superior to previous fatty oil technology. This combination of additives provides excellent extreme pressure properties when pipe threading, tapping, reaming, or broaching. PROCUT SS is designed for the most demanding metal removal applications. It is particularly well suited to the machining of stainless steels. PROCUT SS has low misting properties, an effective defoamer package, and contains no active sulfur. It can be used on copper and its alloys and as a dual-purpose oil.

TYPICAL PROPERTIES

Viscosity @ 100°F, SUS	180
Flash Point, °F	390
Pour Point, °F	10
Gravity, API	13.5
Color, ASTM	4.5

SHIPPING CONTAINERS

Available in 5 gallon pails, 55 gallon drums, or 275 gallon bulk containers.

HEALTH & SAFETY

Material Safety Data Sheets are available for all Wallover products. Consult the MSDS for information regarding the storage, handling and disposal of this product.

WARRANTY

All reasonable effort has been made to ensure that the information provided in this publication is accurate. No warranties are expressed or implied since the use of this product is beyond our control.