

### WOCOTEC 3200 SERIES RUST PREVENTIVES

WOCOTEC 3200 series of products are blended with a 140°F (min.) flash point solvent and are straw to amber in color. These products are water displacing, non-staining rust preventives which will not emulsify even in the presence of alkali, and will quickly separate water displaced from metal surfaces after machining operations or alkali cleaning. The protective film left on the metal after evaporation of the solvent is ultra-thin, non-staining highly protective and dry. These products can be removed with mineral spirits, kerosene or alkali wash.

WOCOTEC	<u>3205</u>	<u>3208</u>	<u>3212</u>	<u>3214</u>
Viscosity @100°F , SUS	30	31	32	32
Flash point, °F	142 min.	142 min.	142 min.	142 min.
Humidity Cabinet, Days	35	50	60+	60+
Indoor Storage, Months	3	6	9	12+

#### SHIPPING CONTAINERS

Available in 5 gallon pails, 55 gallon drums or 275 gallon bulk containers.

#### HEALTH & SAFETY

Material Safety Data Sheets are available for all Wallover products. Consult the MSDS for information regarding the storage, handling and disposal of this product.

#### WARRANTY

All reasonable effort has been made to ensure that the information provided in this publication is accurate. No warranties are expressed or implied since the use of this product is beyond our control.